

# GILGEN FD 20 SWING DOOR DRIVE UNIT



**GILGEN**  
GILGEN DOOR SYSTEMS

# POWERFUL, BUT QUIET-RUNNING



The robust Gilgen FD 20 swing door drive unit is designed for quiet, reliable operation.

---

## GILGEN FD 20 SWING DOOR DRIVE UNIT

- 2 Powerful, but quiet-running
- 4 Simply more user-friendly
- 6 Whatever you need ...
- 8 Day-to-day reliability
- 10 Maximum user-friendliness
- 12 Fire prevention and emergency exits
- 14 Easy installation – Maximum efficiency
- 16 Selection and planning criteria
- 18 selection and planning criteria



# SIMPLY MORE USER-FRIENDLY



The Gilgen FD 20 swing door drive unit is designed for the automation of new or existing doors.

# From light internal doors to heavyweight external doors

The Gilgen FD 20 swing door drive unit makes doors significantly easier to operate. Contactless opening and closing also fulfils the most demanding hygiene requirements, while helping to ensure trouble-free entry and exit.

## Flexible, functional applications

Wherever people work, living and are cared for or congregate, there are doors that tend to hinder their comings and goings. The automation of these doors offers smooth access with hygienic, obstacle-free entry and exit.



## Possible configurations

- Single door leaf and bi-parting
- Emergency-exit function
- Fire-safety function
- Special solutions

## Versatile application

Gilgen swing door drive units are ideal for new installations or building upgrades. Lightweight doors, external doors and even fire doors can be automated with ease.

## Individual

Thanks to the wide range of options available, the user is sure to obtain a fully-customised, automatic door.

## Smooth, quiet operation

The electromechanical drive unit ensures that the door operates quietly and smoothly.


## Maximum reliability

The use of top-quality components guarantees reliability to match, plus a long service life and minimal maintenance.

## Automatic hygiene

Contactless user-access helps eliminate the risk of germ contamination. This feature is of particular importance, and taken very seriously, in public places such as hospitals, care homes, clinics and toilets.

# WHATEVER YOU NEED ...



## Functional

The wide range of available options delivers customer-specific automatic solutions.



# One drive mechanism – many possible applications

The Gilgen FD 20 swing door drive unit is highly consistent when it comes to performance, long service life and quiet running. From light internal doors to heavyweight external doors designed to withstand high winds – the Gilgen FD 20 is always the right choice!

A reliable drive mechanism for virtually any application combined with the right accessories.

The smooth lines of the Gilgen FD 20 make it compatible with any architectural design. It adds value to the various applications in which it is used, thereby enhancing the overall aesthetic approach.



Escape-way / Emergency exit



Heavyweight external doors



Low-Energy mode



Bi-parting installations



Interlock function

## Adjustable functions

- Low-Energy / full-power
- Safety monitoring with automatic stop/reverse mechanism
- Wind-load regulation
- Control of opening and closing speed, hold-open time and motor power
- Push & Go Function
- Automatic closing sequence control for bi-parting configurations

- Reinforced closure (forced engagement of lock)
- Acoustic signal during movement of the door leaf


## Optional / Extendable

- Connection of electric locks / locking mechanism
- Remote-control systems
- Casing in stainless steel or aluminium

- Fully-enclosed housing
- Integrated opening end-stop
- Inverted drive configuration
- Operating-status display:
  - In the drive mechanism or on an external control unit
  - Acoustic: door opens/closes
  - Dry contact for transmission of data to the building's central control system

# DAY-TO-DAY RELIABILITY

Gilgen automatic doors offer maximum user-friendliness combined with advanced safety features.






# Available safety and security elements

Automatic doors used in the public sector have to conform to EN 16005. Various configurations are possible, depending on the application. The specialists at Gilgen Door Systems will be pleased to answer any questions that you might have.

Swing door drive units supplied by Gilgen Door Systems are fully certified, and designed to conform to the highest quality and safety specifications.

The robust design of the Gilgen FD 20 makes it resistant to attack.



Safety sensors with "Reverse" and "Stop" functions offer additional protection for pinch points. The "blanking" function is configured via the drive unit to guarantee optimum performance.



Finger protection



Activ infrared safety sensor

## Safety-tested

The TÜV-tested drive mechanism is designed to ensure smooth, automatic operation. A series of compatible safety elements ensures optimum protection. If the Low-Energy function is configured, the system can even do without safety sensors.

## Optional / extendable

- TÜV-tested sensor strip or light barriers
- Potential-free contact for «Door in Operation» indication signal
- Emergency OFF switch
- Finger protection
- Active infrared light detector

# MAXIMUM USER-FRIENDLINESS



## Obstacle-free entry and exit

When you are in a hurry and your hands are full, the Gilgen FD 20 offers contactless, obstacle-free access.

# Simple to operate

Hands-free access is provided by a movement sensor or other impulse elements. The operating modes of the Gilgen FD 20 are easy to configure using the corresponding illuminated program selector keys.

## Control elements

- Radar
- Sensor
- Contactless detection sensor
- Remote radio control F9000
- Foot- or elbow-operated switch
- Key-operated (pivoting) switch for operating the locked door
- D-BEDIX external control unit
- etc.



Contactless detection sensor



Radar



Remote radio control F9000

## Program selector keys

The buttons on the side of the drive mechanism are used to select the desired operating mode. The selected button lights up to give an immediate indication of the active operating mode. The buttons can be disabled, depending on the situation. All settings can likewise be configured with the optional D-BEDIX control unit.



Integrated program selector keys



D-BEDIX (optional)



# FIRE PREVENTION AND EMERGENCY EXITS



Gilgen FD 20-F – tried and tested components keep your building safe, including in an emergency.

# Tried and tested quality for emergencies

The fire rated Gilgen FD 20-F swing door drive unit is available with a number of additional safety features to ensure controlled operation in the event of an emergency.

Automatic emergency exits and fire-/smoke-proof doors offer convenience for everyday use, while fulfilling legal requirements, including in the event of an incident. These additional functions also increase the range of possible applications. Gilgen automatic doors meet the highest quality, safety and security specifications.



Emergency exit



Fire barrier



Panic exit

## **Reliable protection from smoke and fire and a safe emergency exit/rescue access.**

If a fire alarm is activated, the door closes under full control from any position. The smoke and fire barrier can then be opened manually for use as an escape route/emergency exit.

Drive mechanisms with the "Invert" function enabled are ideal for building smoke-extraction/ventilation purposes, and for escape routes/emergency exits. The doors are opened by spring pressure and closed again by motor. This ensures, in the event

of a power failure or fire emergency, that the door can be opened safely to allow heat and smoke to dissipate in a controlled manner. There is thus no need for an emergency power supply in this respect.

# EASY INSTALLATION – MAXIMUM EFFICIENCY



The Gilgen FD 20 is designed for quick and simple installation.



# Drive technology and functionality combined

The compact, lightweight Gilgen FD 20 swing door drive unit is characterised not only by its advanced technology and functionality, but also by its fast installation and startup.

## Guided initial startup

Once the Gilgen FD 20 has been installed, the integrated, user-friendly joystick and LC-Display can be used to set the relevant parameters (opening and closing time, safety monitoring, reinforced closure etc.). The final step is to adjust the power of the return spring to the corresponding size of door.



The LC-Display integrated into the drive mechanism provides the user with guidance for initial startup. No additional external devices are required.



The illuminated program selector keys and master switch (all-pole) are integrated into the side cover for intuitive operation.



The selectable Low-Energy function makes additional safety sensors unnecessary. The changeover is carried out without any additional upgrade cards.

# SELECTION AND PLANNING CRITERIA

Choose the right type of installation  
for your needs.



# Installation and configuration options

Various installation and configuration options are offered to match requirements. Find out which variant is the best for you:

## Lintel installation / sliding rod

pushing function



- aesthetic solution



## Lintel installation / sliding rods

pulling function



- aesthetic solution



## Lintel installation / standard rods

pushing function



- unbeatable transformation of power



## Installation on door leaf / sliding rods

pushing function

- appropriate for slight lintel heights





# OUR TECHNOLOGY IN DETAIL




Find out all what's hidden workings of the  
Gilgen FD 20 swing door drive unit.

# Technical specifications - overview

## Application limits:

Max. leaf weight	250 kg
Door sizes EN 3-7	(850 – 1600 mm)
Door sizes fire doors EN 4-6	(950 – 1400 mm)
Max. opening angle	105°
Tested in accordance with	DIN 18650, EN 16005
	<i>Fire-prevention version included in approval procedure</i>

## Application limits with sensory system / Low-Energy



## Technical specifications:

Power transfer	Standard rods (pushing function) Sliding rods (pushing and pulling function)
Dimensions of drive mechanism	height 95 mm, width 690 mm, depth 120 mm
Weight of drive mechanism	10,5 kg
Ambient temperature	-15 to +50 °C
Protection rating	IP 40
Operating voltage	230 VAC (+10/-15 %), 50 Hz, 10/13 A
Power consumption of drive mechanism	max. 560 W
Rated motor capacity	100 W
Power supply,	
external user	24 VDC (±10 %), 2 A
Output shaft torque	max. 80 Nm
Lintel depth standard rods	max. 250 mm
Lintel depth sliding rods	-30 / +140 mm
Opening speed	max. 40°/s
Closing speed	max. 40°/s
Relative humidity	max. 85 %

# Maximum wind-load capacity with sliding rods


The data in the following tables correspond to fully-secured doors with safety-sensor systems. The presented application limits result from wind-load, door size and type of rods.

### Sliding rods


Swing door drive units with sliding rods and pushing / pulling function are the most common and best looking, building solution.



### Sliding rods pushing function (outward-opening door)



### Sliding rods pulling function (inward-opening door)




## ... plus standard rods

### Standard rods

Our swing door drive units with standard rods and pushing function are the most efficient way to harness the force of the Gilgen FD 20 system.




### Standard rods pushing function (outward-opening door)



The Gilgen FD 20 drive unit for swing doors is capable of reliably opening and closing doors even if exposed to wind speeds of up to 80 km/h (320 Pa). For external doors, Gilgen Door Systems recommends to assume a wind pressure of at least 100 Pa (45km/h). Doors installed in certain exposed locations (e.g. near the sea, in mountainous regions, on observation platforms, et.) are often subject to higher wind loads.



# LET US OPEN DOORS FOR YOU



Get in touch with us.  
We look forward to hearing from you!

Headquarters  
Gilgen Door Systems AG  
Freiburgstrasse 34  
CH-3150 Schwarzenburg  
Tel. +41 31 734 41 11  
Fax +41 31 734 43 79  
[www.gilgendoorssystem.com](http://www.gilgendoorssystem.com)

Sales Switzerland  
Gilgen Door Systems AG  
Untermattweg 22  
3027 Bern  
Tel. 0848 80 44 88  
Fax 031 985 36 01  
[www.gilgendoorssystem.ch](http://www.gilgendoorssystem.ch)

Gilgen Door Systems AG  
In der Au 5  
CH-8406 Winterthur  
Tel. 0848 80 44 88  
Fax 052 268 90 10  
[www.gilgendoorssystem.ch](http://www.gilgendoorssystem.ch)

Gilgen Door Systems AG  
Route des Avouillons 30  
CH-1196 Gland  
Tel. 0848 80 44 88  
Fax 022 999 60 80  
[www.gilgendoorssystem.ch](http://www.gilgendoorssystem.ch)

Dansk leverandør:

**Swissdoor ApS**  
Stenhuggervej 2  
5471 Søndersø  
Danmark  
Tlf. +45 86 28 00 00  
[mail@swissdoor.dk](mailto:mail@swissdoor.dk)  
[www.swissdoor.dk](http://www.swissdoor.dk)

Gilgen Door Systems Germany GmbH  
Münchener Strasse 22  
DE-64521 Gross-Gerau  
Tel. +49 61 52 92 52 60  
Fax +49 61 52 92 52 70  
[www.gilgendoorssystem.de](http://www.gilgendoorssystem.de)

Gilgen Door Systems Austria GmbH  
Concorde Business Park 1 / E / 1 / 4  
AT-2320 Schwechat  
Tel. +43 17 06 58 66  
Fax +43 17 06 58 56  
[www.gilgendoorssystem.at](http://www.gilgendoorssystem.at)

Gilgen Door Systems France Sàrl  
21, rue Alexis de Tocqueville  
Silic 5 - Immeuble Ampère  
FR-92182 Antony Cedex  
Tel. +33 1 46 66 66 80  
Fax +33 1 56 45 29 66  
[www.gilgendoorssystem.fr](http://www.gilgendoorssystem.fr)

Gilgen Door Systems UK Limited  
Crow House, Crow Arch Lane,  
GB-Ringwood, Hampshire, BH24 1PD  
Tel. 01425 462000  
Fax. 01425 462001  
[www.gilgendoorssystem.co.uk](http://www.gilgendoorssystem.co.uk)

Gilgen Door Systems Italy S.r.l.  
Via della Fisica, 4  
IT-40068 San Lazzaro di Savena (BO)  
Tel. +39 051 70 49 45  
Fax +39 051 63 25 099  
[www.gilgendoorssystem.it](http://www.gilgendoorssystem.it)

Gilgen Door Systems Spain  
Tel: +34 93 590 71 94  
Fax +34 93 590 71 94  
[www.gilgendoorssystem.es](http://www.gilgendoorssystem.es)

Gilgen Door Systems (Suzhou) Co. Ltd  
Building 1-C  
128 Fangzhou Road  
Suzhou Industrial Park  
CN-215126 Suzhou  
Tel: +86 512 62 83 87 93  
Fax +86 512 62 83 37 10  
[www.gilgendoorssystem.cn](http://www.gilgendoorssystem.cn)